

Specifications



Photo is representative



Eaton FAZ-C25/1-DC

Eaton FAZ supplementary protector,UL 489 Industrial miniature circuit breaker - supplementary protector,Medium levels of inrush current are expected,25 A,10 kAIC,Single-pole,125 Vdc per pole,5-10X /n,50-60 Hz,Standard terminals,C Curve

General specifications

PRODUCT NAME	Eaton FAZ supplementary protector
CATALOG NUMBER	FAZ-C25/1-DC
EAN	4015082791308
PRODUCT LENGTH/DEPTH	0.7 in
PRODUCT HEIGHT	4.13 in
PRODUCT WIDTH	2.97 in
PRODUCT WEIGHT	1 lb
WARRANTY	1 year
CERTIFICATIONS	UL 489 CSA Std. C22.2 No. 235
CATALOG NOTES	Positioned for medium inrush startup currents to provide protection for small transformers and pilot devices.

Physical Attributes

NUMBER OF POLES	Single-pole
TERMINALS	Standard
TYPE	UL 489 Industrial miniature circuit breaker - supplementary protector

Miscellaneous

APPLICATION	Suitable for applications where medium levels of inrush current are expected
-------------	--

Performance Ratings

AMPERAGE RATING	25 A
CIRCUIT PROTECTION	C curve
FREQUENCY RATING	50-60 Hz
INTERRUPT RATING	10 kAIC
TRIP TYPE	5-10X /n
VOLTAGE RATING	125 Vdc

Resources

CATALOGS	Circuit Protection, Miniature Circuit Breakers and Supplementary Protectors, Volume 4, Tab 1
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - FAZ-C25/1-DC

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

