

Specifications

Photo is representative

Eaton FAZ-C7/2-RT

Eaton FAZ branch protector,UL 1077
Industrial miniature circuit breaker -
supplementary protector,Medium levels of
inrush current are expected,7 A,15
kAIC,Two-pole,277/480 V,5-10X /n,50-60
Hz, Ring-tongue terminals,C Curve

General specifications

PRODUCT NAME	Eaton FAZ branch protector
CATALOG NUMBER	FAZ-C7/2-RT
EAN	4015081020812
PRODUCT LENGTH/DEPTH	1.38 in
PRODUCT HEIGHT	2.5 in
PRODUCT WIDTH	4 in
PRODUCT WEIGHT	0.92 lb
WARRANTY	1 year
CERTIFICATIONS	IEC 60947-2 CSA Std. C22.2 No.235 UL 1077
CATALOG NOTES	Positioned for medium inrush startup currents to provide protection for small transformers and pilot devices.

Physical Attributes

NUMBER OF POLES	Two-pole
TERMINALS	Ring-tongue
TYPE	UL 1077 Industrial miniature circuit breaker - supplementary protector

Miscellaneous

APPLICATION	Suitable for applications where medium levels of inrush current are expected
-------------	--

Performance Ratings

AMPERAGE RATING	7 A
CIRCUIT PROTECTION	C curve
FREQUENCY RATING	50-60 Hz
INTERRUPT RATING	15 kAIC
TRIP TYPE	5-10X /n
VOLTAGE RATING	277/480V

Resources

CATALOGS	Circuit Protection, Miniature Circuit Breakers and Supplementary Protectors, Volume 4, Tab 1
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - FAZ-C7/2-RT

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

