

Specifications



Photo is representative



Eaton XTCE050D00TD

Eaton XT IEC contactor, 50A, 24-27 Vdc, 0NO-0NC, 50A, Frame D, 55 mm, 3, 7.5, 10/ 15, 20, 40, 50 hp (1/3PH @115, 200, 230/200, 230, 460, 575 V), Three-pole, Non-reversing, , Screw terminals, FVNR

General specifications

PRODUCT NAME	Eaton XT IEC contactor
CATALOG NUMBER	XTCE050D00TD
EAN	4015082778446
PRODUCT LENGTH/DEPTH	5.77952756 in
PRODUCT HEIGHT	4.09448819 in
PRODUCT WIDTH	2.16535433 in
PRODUCT WEIGHT	0.61729433 lb
COMPLIANCES	CE Marked RoHS Compliant
CERTIFICATIONS	UL Listed CSA Certified IEC 60947 EN 60947
CATALOG NOTES	Screw terminals (6-65A); 5 mm (80-150A); no lugs (185-2000A)



Powering Business Worldwide

Product specifications

AMPERAGE RATING	50A
HP RATING - MAX	3, 7.5, 10/ 15, 20, 40, 50 hp (1/3PH @115,200,230/200,230,460,575 V)
NUMBER OF POLES	Three-pole
TYPE	Full voltage non-reversing contactor
FRAME SIZE	55 mm
TERMINALS	Screw terminals
COIL VOLTAGE	24-27 Vdc
CONTACT CONFIGURATION	0 NO, 0 NC
CONTINUOUS AMPERE RATING	50 A
SERIES	XT IEC
OPERATION	Non-reversing

Resources

CATALOGS

[Motor Control and
Protection, IEC Contactors
and Starters, Volume 5,
Tab 1](#)

SPECIFICATIONS AND DATASHEETS

[Eaton Specification Sheet -
XTCE050D00TD](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

