

HALF-SIZE RELAYS



Active

See All Documentation

TE CONNECTIVITY
HFW1101K06 = M39016/6-129L

HFW1101K06
TE Internal Number: 1-1617028-4
Mil-Spec: M39016/6-129L

Not EU RoHS or ELV Compliant
Find Compliant Alternatives

Contact Arrangement 2 Form C, DPDT, 2 C/O

Input Voltage(VDC) 26.5

Contact Current Rating(A) 2

Coil Voltage Rating(VDC) 26.5

Coil Resistance(Ω) 700
See All Features

North America

DISTRIBUTOR	QUANTITY	DATE AS OF
FLAME ENTERPRISES 800-854-2255	8	2015/08/26

SAVE TO LIST

CHECK FOR TOOLING

FIND SIMILAR PRODUCTS

DOCUMENTATIONFEATURES

Please review product documents or contact us for the latest agency approval information.

Product Type Features	Coil Latching	Without
	Product Type	Relay
	MOSFET Driver	Without
	Relay Type	Military/Aerospace High Performance
	Enclosure Type	Hermetically Sealed

Configuration Features	Transistor Driver	Without
------------------------	-------------------	---------

Electrical Characteristics	Input Voltage(VDC)	26.5
	Coil Voltage Rating(VDC)	26.5
	Coil Resistance(Ω)	700
	Coil Power Rating (DC)(mW)	1003
	Coil Suppression Diode	Without
	Actuating System	DC
	Vibration	30G's, 10 ~ 3000Hz
	Coil Magnetic System	Non-Polarized, Monostable
	Coil Power Measurement	Milliwatts
	Coil Polarity Protection Diode	Without
	Shock	100G's, 6ms

Contact Features	Contact Arrangement	2 Form C, DPDT, 2 C/O
	Contact Current Rating(A)	2

Termination Features	Termination Type	Solder Hook Terminals
----------------------	------------------	-----------------------

Mechanical Attachment	Mounting Type	Plain Case
-----------------------	---------------	------------

Usage Conditions	Operating Temperature Range(°C)	-65 ~ 125
------------------	---------------------------------	-----------

Product Compliance

Statement of Compliance
PDF

VIEW ALL PRODUCT COMPLIANCE

COMPATIBLE

No compatible products found for HFW1101K06