




Datasheet

Item No. 56.704.7855.0

Multi-tier terminal WKFN 4 E/D/SL/35

Multi-tier terminal block with spring clamp connection for mounting on TS 35, nominal cross section 4 mm², width 6 mm, color gray



Item No.	56.704.7855.0
EAN	4015573767676
order unit	100 Piece(s)

Approvals







Technical data

General

Nominal cross section	4 mm²
Colour	Grey
Number of levels	2
Number of clamp positions per level	2
Width/grid dimension	6 mm
Insulating housing	PA666
Inflammability class of insulation material acc. with UL94	V0
Explosion-tested version "EEx e"	No
Mounting method	DIN rail (top hat rail) 35/7.5 mm
Terminal blocks for electrical installations	Yes

Technical data

100111101111111111111111111111111111111	
Rated current	32 A
Rated voltage	500 V
Rated impulse voltage	6 kV
Pollution degree	3
Closing plate required	Yes
Length	90.1 mm
Type of insulation material	Thermoplastic

Connection Data

Connection type 1	Tension clamp connection
Connection type 2	Tension clamp connection





Minimum cross section solid	0.13 mm ²
Maximum cross section solid	6 mm²
Minimum cross section fine stranded	0.13 mm²
Maximum cross section fine stranded	4 mm²
Wire strip length	11 mm

Technical Data UL/CSA

Cross section UL	24-10 AWG
Voltage UL	300
Current factory wiring	30 A
Current field wiring	30 A
Cross section CSA	24-10 AWG
Voltage CSA	300 V
Current CSA	32 A

Accessories

Тур:	Description:
Warning cover ADF 4/4 YELLOW	Cover with warning symbol for DIN rail terminal blocks type WKF
Mounting rail 35x27x7,5EN60715 2000MM	Mounting rail TS 35, unslotted, size 7,5 mm, length 2 m, material steel. galv. zinc-plated and dichromated
Mounting rail 35x27x7,5EN60715 2000MM	Mounting rail TS 35, slotted, size 7,5 mm, length 2 m, material steel. galv. zinc-plated and dichromated
Mounting rail 35x27x7,5EN60715 2000MM	Mounting rail TS 35, slotted, size 7,5 mm, length 2 m, material steel. galv. zinc-plated and dichromated
Mounting rail 35x24x15 EN60715 2000MM	Mounting rail TS 35, unslotted, size 15 mm, length 2 m, material steel. galv. zinc-plated and dichromated
Mounting rail 35x24x15 EN60715 2000MM	Mounting rail TS 35, unslotted, size 15 mm, length 2 m, material steel, hot galvanized
Mounting rail 35x27x15(EN60715)2000MM	Mounting rail TS 35, unslotted, size 15 mm, length 2 m, material steel. galv. zinc-plated and dichromated
Mounting rail 35x27x15(EN60715)2000MM	Mounting rail TS 35, slotted, size 15 mm, length 2 m, material steel. galv. zinc-plated and dichromated
Mounting rail 35x24x15 EN60715 2000MM	Mounting rail TS 35, unslotted, size 15 mm, length 2 m, material E copper
Test plug ST 2 / 2.3 RED	Test plug 2,3 mm color red
Jumper bar IVBWKF 4- 2	Cross connector, insulated for DIN rail terminal blocks type WKF, 2 -pole
Jumper bar IVBWKF 4 - 3	Cross connector, insulated for DIN rail terminal blocks type WKF, 3 -pole
Jumper bar IVBWKF 4 - 4	Cross connector, insulated for DIN rail terminal blocks type WKF, 4 -pole
Jumper bar IVBWKF 4 - 5	Cross connector, insulated for DIN rail terminal blocks type WKF, 5 -pole
Jumper bar IVBWKF 4 - 6	Cross connector, insulated for DIN rail terminal blocks type WKF, 6 -pole
Jumper bar IVBWKF 4 - 7	Cross connector, insulated for DIN rail terminal blocks type WKF, 7 -pole
Jumper bar IVBWKF 4 - 8	Cross connector, insulated for DIN rail terminal blocks type WKF, 8 -pole
Jumper bar IVBWKF 4 - 9	Cross connector, insulated for DIN rail terminal blocks type WKF, 9 -pole
Jumper bar IVBWKF 4- 10	Cross connector, insulated for DIN rail terminal blocks type WKF, 10 -pole
	Warning cover ADF 4/4 YELLOW Mounting rail 35x27x7,5EN60715 2000MM Mounting rail 35x27x7,5EN60715 2000MM Mounting rail 35x27x7,5EN60715 2000MM Mounting rail 35x24x15 EN60715 2000MM Mounting rail 35x24x15 EN60715 2000MM Mounting rail 35x27x15(EN60715)2000MM Mounting rail 35x27x15(EN60715)2000MM Mounting rail 35x27x15(EN60715)2000MM Test plug ST 2 / 2.3 RED Jumper bar IVBWKF 4 - 2 Jumper bar IVBWKF 4 - 3 Jumper bar IVBWKF 4 - 6 Jumper bar IVBWKF 4 - 6 Jumper bar IVBWKF 4 - 7 Jumper bar IVBWKF 4 - 8 Jumper bar IVBWKF 4 - 8 Jumper bar IVBWKF 4 - 9





Drawings

