

Datasheet

Art.No. 81.000.6210.0

Fuse module 24V DC WIPOS FM 4-10

wipos FM 4-10, Fuse Module 24 V DC, for 4 fuses 5 x 20 mm, with general fault signal (N.O. contact), Mounting on DIN Rail TS35, supply with double clamp, LED status indication per fuse, max. 10A per fuse holder, total output current of 4 fuses: max. 40 A at 23°C, Operating voltage range: 18 - 30 V DC, W x H x D: 48 x 96 x 68 mm



Art.No.	81.000.6210.0
EAN	4049088116551
Order unit	1 pieces

Approvals



Technical data

General

Connection type	Screw connection
Rail mounting possible	Yes

Technical data

Type of output voltage	DC
Output voltage	24 V
Input voltage DC min.	24 V
Input voltage DC max.	24 V
Input current, max.	40 A
Fuse insert	G-fuse 5x20 mm
Rated fuse current, max.	10 A
Display	LED
General fault signal	potential-free semiconductor output
Switching output	18-30 V DC / max. 0,1 A
Connector cross section (input)	10 mm ² solid/stranded
Connector cross section (output)	0,14-4 mm ² solid / 0,14 - 2,5 mm ² stranded

Dimensions

Depth	68 mm
Width	48 mm
Height	96 mm