



# Datasheet

Item No. 96.022.4453.1

## Male connector with strain relief RST20I2S S13ZRW V §

Connector RST20i2, 2 pole, male, screw connection, 250V/20A, for illumination cable, color of coding: black, color of housing: blac



| Item No.   | 96.022.4453.1 |
|------------|---------------|
| EAN        | 4015573780880 |
| order unit | 100 Piece(s)  |

## Technical data

#### General

| 0.10.11                          |       |
|----------------------------------|-------|
| Rated current                    | 20 A  |
| Rated voltage                    | 250 V |
| Rated impulse voltage            | 4 kV  |
| Pull relief                      | Yes   |
| Pollution degree                 | 3     |
| Mechanical coding                | Yes   |
| Interlockable                    | Yes   |
| Color of coding/ contact carrier | Black |

#### Connection Data

| Connection cross section solid    | 4 mm² |
|-----------------------------------|-------|
| Connection cross section stranded | 4 mm² |
| Terminations per pole             | 1     |

# Model

| Model                     | Plug             |
|---------------------------|------------------|
| Number of poles           | 2                |
| Connection type           | Screw connection |
| Degree of protection (IP) | IP66/IP68        |

### Material

| Housing material                            | Polyamide     |
|---|---------------|
| Halogen free                                | Yes           |
| Contact material                            | CuZn          |
| Insulation components continous temperature | 100 °C        |
| Surface finish                              | Silver-plated |

## Dimensions

| Length | 80.4 mm |
|--------|---------|
| Width  | 34.6 mm |
| Height | 34.6 mm |





### Drawings

