

[All Categories](#) > [Sensing](#) > [Limit Switches](#) > [Basic Switches](#) > [Z-15](#) > Item # Z-15GD-BC

Item # Z-15GD-BC, 4.2 mm Mounting Hole Size Single Pole Double Throw (SPDT) Contact Configuration Quick connect Terminal Basic Switch

Request Information

[Printable Page](#)

[Download PDF](#)

[Email This Page](#)



Precision Basic Switches

DOWNLOADS

[Z-15 High Precision Basic Switches Data Sheet](#)

Specifications

Type	Basic Switch
Terminal Type	Quick Connect Terminal
Contact Configuration	Single Pole Double Throw (SPDT)
Actuator Type	Short Plunger
Rated Load Current at 250 V Alternating Current (AC) Voltage	15 A
Inrush Current at Normally Closed (NC) Contact Configuration	Up to 30 A
Inrush Current at Normally Open (NO) Contact Configuration	Up to 15 A
Mounting Hole Size	4.2 mm
Electrical Operations [Min]	500,000
Electrical Operating Frequency [Max]	20 OPM
Mechanical Operations [Max]	240 OPM

News

[Product News](#)

[Corporate News](#)

Company Info

[About Omron](#)

[Omron Principles](#)

Careers

[Awards](#)

[Giving Back](#)

Contact

[Omron in United States](#)

[Contact Us](#)

Follow us

[Facebook](#)

Omron on Social Media
eNews

Company Profile
Business Fields
Events
Giving Back
Environmental

Summer Internships

Global presence

 Twitter

 LinkedIn

 Youtube

[Omron Americas](#) [Omron Corporation](#) [Legal Notices](#) [Privacy Policy](#) [Sitemap](#)

Copyright © Omron Corporation 2017. All rights reserved.
