

Representative

Catalog Number: A72

 Product ID:
 7TAI029630R0015

 UPC Number:
 78621080800

Status: Active

Non-Insulated Ring Terminal, Length .92 Inches, Width .50 Inches, Bolt Hole 5/16 Inch, Wire Range #22-#16 AWG, Copper, Tin Plated, 1,000 Pack

- These non-insulated ring terminals are made of electrolytic copper for high conductivity.
- They can be installed with crimping tools having a single indentor or double indentor (recommended for solid wire).
- · Serrated barrel increases grip on wire.
- Application Tools: WT110M, WT111M, WT112M, WT2000, ERG4002
- Alternate Package Qty: A18-516

North American Specifications (UNSPSC)		
UNSPSC	39121432 Electrical terminals	
IGCC	4603 Electrical terminals	
Brand Name	Sta-Kon	
Туре	Ring Terminal	
Special Features	These non-insulated ring terminals are made of	
	electrolytic copper for high conductivity. They can	
	be installed with crimping tools having a single in-	
	dentor or double indentor (recommended for solid	
	wire). Serrated barrel increases grip on wire.	
Standard	UL E9809	
Wire Size	22-16	
Voltage Rating	600V	
Material	Copper	
Color	Metallic	

European Specificatio	ns (ETIM)
ETIM	EC001052 Solderless copper terminals for copper
	conductors
Flange shape	Ring shape
Insulation	None
Reel packaging	N
AWG-range	22-16
Material	Copper
Surface protection	Tinned

Packaging	
Inner Quantity	1000
Inner Dimensions (inches)	4x4x3
Outer Quantity	10000
Outer Dimensions (inches)	21.5x8.5x3.5
Weight Uom	1.88 lbs. per 1000

Documents / Support Tools

Technical Drawing / Data Sheet WSD-000188

For further technical assistance, please contact us...

ABB Installation Products Technical Support MS 3B-50

860 Ridge Lake Blvd. Memphis, TN 38120 s Technical Support F N F

Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321



Email:techsupport@tnb.com